

TELEDEX

iPhone RediDock



iPhone SIP DECT Cordless

SIP DECT CORDLESS SERIES

Cordless VoIP DECT phone that supports multiple RediDock™ Handsets within the room.

iPhone TELEDEX

Full-featured. Rock solid.

A Cetus, Inc. brand.



SIP DECT CORDLESS TECHNOLOGY FOR VoIP.



Teledex iPhone SIP NDC series phones marry DECT technology with IP telephony to provide a cordless phone for your VoIP infrastructure. Utilizing the latest in DECT technology, Teledex iPhone SIP cordless phones won't interfere with your 2.4 GHz WiFi networks. And with RediDock you can deploy one full cordless phone (handset and base unit) and up to three additional handsets within the same room or suite.

Teledex iPhone IP phones are tested and approved for interoperability with major hospitality IP-PBX solutions. You get full-featured, rock solid performance, coupled with powerful management tools and support resources that reduce headaches for you.

- Single or Two line DECT configuration
- SIP based protocol
- SIP RFC 3261 compliant
- Codecs supported: G711a; G711µ; G729
- 2-port 10/100 ethernet switch
- Supports 802.1Q VLAN tagging
- Supports DHCP or static IP address
- AutoSync – handset automatically syncs with base unit when in cradle
- Speakerphone
- Supports up to 3 additional iPhone RediDock kits per base
- 5 or 10 programmable guest service keys
- Hold, Mute, Conference*, Redial keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Bright message waiting indicator and positive charge indicator
- morePhone™ Overage Program with each qualifying shipment of Teledex telephones includes extra sets at no charge.
- 5-Year Warranty

**Two-line models only
Visit www.teledex.com for the latest VOIP switch certifications.*

SIP DECT CORDLESS SERIES

SPECIFICATIONS

Standard Colour: Ash and Black	Standby time: 14 days Part 15, Subpart J,
Footprint: 6.0" x 9.0" (15.2cm x 22.9cm)	Talk time: 4 hours Class A, Part 68
Footprint (RediDock): 2.75" x 8.17" (7.0cm x 20.08cm)	Humidity:65% ± 20%	Safety Standard: ETL and CE
Weight: 2.0 lbs. (0.9kg)	Temperature: 77°F ± 50° (25°C ± 10°C)	Operating Voltage: 24 to 56 VDC Non-Polarity
Weight (Redidock) 7 oz. (0.2kg) (without handset)	Packaging: 12 per carton	Flash Timing: 600 ms
..... 12 oz. (0.34kg) (with handset)	Packaging (RediDock): 20 per carton	Ringer Equivalence: Z (Use only behind PBX)
Frequency: 1.9 GHz or 1.8 GHz	Faceplate Size: Full length	Handset: Hearing Aid compatible
Power: PoE or local adapter	FCC Specifications: Meet or exceeds	Line Cord: 15-foot, 2 RJ45

Part Numbers

DECT 1.9GHz CORDLESS (Single-line) NDC2105s (5-button speaker)

IPN96459IP Ash
IPN964591IP Black

NDC2110s (10-button speaker)

IPN96559IP Ash
IPN965591IP Black

RediDock 1.9 GHz (Single-line)

IRD9110-POE

IPN965591PHDKIT Ash
IPN9655911PHDKIT Black

DECT 1.9GHz CORDLESS (Two-line) NDC2205s (5-button speaker)

IPN98459IP Ash
IPN984591IP Black

NDC2210s (10-button speaker)

IPN98559IP Ash
IPN985591IP Black

RediDock 1.9 GHz (Two-line)

IRD9210-POE

IPN985591PHDKIT Ash
IPN9855911PHDKIT Black

DECT 1.8GHz CORDLESS (Single-line) No Part Numbers found

DECT 1.8GHz CORDLESS (Two-line) No Part Numbers found



Continuing the tradition.

To learn more, or to place an order, please visit www.Teledex.com, call +1 719 638 8821 or email sales@teledex.com.